

Instruction Booklet

CUBE (RX-202)

Please read all instructions
carefully before opening box



1


PULL YOUR REXframe®
FABRIC OUT OF THE BOX
& UNWRAP YOUR
EXTRUSION

CAREFUL NOT TO CUT
INTO THE BAGS OR THE BOX
AS YOU COULD DAMAGE
THE FABRIC



2


INSERT THE RX-105 LENGTHS INTO THE RX-202 KNUCKLE
AS SHOWN



RX-202 Knuckle


3

CONTINUE TO INSERT THE HORIZONTAL RX-105 LENGTHS. LOCK THEM INTO PLACE BY INSERTING THE SUPPLIED SCREWS AND TIGHTENING WITH AN ALLEN KEY




4

ONCE THE RX-105 LENGTHS ARE IN PLACE, INSERT THE UPRIGHT RX-107 POSTS





5

INSERT SCREWS AND
TIGHTEN WITH AN
ALLEN KEY



6

ALIGN THE FEET TO THE
PRE-DRILLED HOLES ON
THE BOTTOM LENGTH AND
INSERT SUPPLIED SCREWS





7

TIGHTEN THE SCREWS
USING THE ALLEN KEY

Inserting HD Feet

8

INSERT THE FABRIC INTO THE EXTRUSION STARTING WITH THE CORNERS ENSURE THE SILICON GASKET IS CONCEALED




9

FOLLOW THE DIAGRAM BELOW FOR THE REMAINING SILICON GASKET EDGE.


STARTING WITH ALL CORNERS

ENSURE SILICON GASKET EDGE ON FABRIC IS PUSHED AS FAR INTO THE CHANNEL AS POSSIBLE, THIS SHOULD SUBSIDE ANY WRINKLES THAT MAY HAVE APPEARED.



Inserting Fabric

10



CONTINUE WITH THE MIDDLE OF EACH LENGTH,
AND THEN THE REMAINDER OF THE FABRIC

11



CONTINUE UNTIL ALL THE FABRIC HAS BEEN FULLY INSERTED